

13 December 1999

Date

Wiley Permission #

TO: William T. Dolling
Vice President, Science and Engineering

Wiley Manuscript

Thiokol Propulsion

Page#/Figure#/Table#

P.O. Box 707

Brigham City, UT 84302

I am preparing a manuscript to be published by John Wiley & Sons, Inc.:

Author/Tentative Title: George P. Sutton/Rocket Propulsion Elements

Estimated Publication Date: Summer 2000 Approximate Number of Pages: 600

I request your permission to include the following material in this and all subsequent editions of my book, including versions made by nonprofit organizations for use of blind or physically handicapped persons, and in all foreign-language translations and other derivative works published or prepared by John Wiley & Sons, Inc. or its licensees, for distribution throughout the world.

Author(s) and/or Editor(s): _____

Title of Book or Periodical: _____

Title of Selection: _____ Copyright Date: _____

From Page: _____, line _____, beginning with the words _____

To Page: _____, line _____, ending with the words _____

Figure# _____ on page _____ Table # _____ on page _____

(If necessary, attach continuation sheets.)

See attached figures 14-8a, 14-8b, 14-9, 14-10, 15-1, 15-3

Please indicate agreement by signing and returning the enclosed copy of this letter. In signing, you warrant that you are the sole owner of the rights granted and that your material doesn't not infringe upon the copyright or other rights of anyone. If you do not control these rights, I would appreciate your letting me know to whom I should apply.

Thank you,

s/G. Sutton

Name

George P. Sutton

11939 Gorham Ave. #302


Los Angeles, CA 90049

Requester's Return Address

AGREED & ACCEPTED

By: *A. L. Lally* Vice President S&E Thiokol Propulsion 1/13/00
Signature Title Date

Credit and/or Copyright Notice _____



RSRM Nozzle Characteristics

Type:	Contoured ✓
TVC	Flexible Bearing ✓
Expansion Ratio	7.72 ✓
Throat Diameter	53.86 in ✓
Exit Diameter	149.64 in ✓
Total Length	178.75 in ✓
Weight	23,941 lb ✓
Maximum Pressure	1,016 psi ✓
Maximum Thrust	3,320,000 lbf ✓
Materials	
Housings	Steel and Aluminum ✓
Liners	Carbon Cloth Phenolic ✓

Figure 14-8a RSRM Nozzle Configuration




Figure 14-8b RSRM Nozzle Components




Figure 14-9 Key parameters which govern design of the nozzle contour




Figure 14-10 Temperature and erosion profiles for the RSRM nozzle

Figure 15-1

Large hybrid rocket booster concept capable of boosting the Space Shuttle. It has an inert fuel grain, a pressurized feed system, and can be throttled





Figure 15-3

Static tests of a 250,000 lbf thrust hybrid motor prototype demonstrated additional work is needed to understand fuel regression and combustion stability issues at large scale.



(Photograph taken with digital camera – see enclosed black and white glossy print or diskette for electronic image.)